

Controlling Triax TDH 700 headend



On location via OSD

5 ways to control your TDH 700 headend and free software for controlling available on www.com.com

- Unique, simple operation via On Screen Display [OSD]
- Programming via PC
- Control and install software via NBOX and TDH Manager [Internet]
- Control and install software via GSM modem and TDH Manager
- Control and install software via telephone modem and TDH Manager
- please see the user manual to make the correct connection of the units and you can also read more on our website about the different solutions



Programming via PC



N-port connection



GSM connection



Telephone modem

Controlling accessories for TDH headend

Type	N-port - for Internet 300766	GSM modem - for mobile phone 300765	Telephone modem - for access 300764
Part No.			
Packing QTY	1	1	1
pcs.			
What you can do	Get access via Internet <ul style="list-style-type: none"> • Install software for NBOX and TDH manager. • Type in the IP address • Select one of the virtual ports • Start controlling the TDH 	Get access via GSM <ul style="list-style-type: none"> • Install software for TDH manager. • Dial up via built-in modem or external standard telephone modem • Insert SIM data card in the GSM modem • Connect the GSM modem to TDH 700 modem port 	Get access via phone modem <ul style="list-style-type: none"> • Install software for TDH manager. • Type in the telephone number • Dial up via built-in modem or external standard telephone modem • Connect the standard telephone modem to TDH 700 modem port
Remarks	Power supply included - see page 111 for connection cable	Power supply not included - see page 111 for connection cable	Power supply included - see page 111 for connection cable

